RRT500 FARM XTREME

MRL®
taking you further

43° LUG ANGLE
PROVIDE BALANCED TRACTION ON BOTH ROADS AND FIELDS.
LOWER FUEL CONSUMPTION



IMPLEMENT FUSION LAYER TECHNOLOGY
PROVIDED/ENSURE STRONG LUG STABILITY
EXTENDED TYRE LIFE



WIDE TREAD WIDTH
PROVIDES BROADER FOOTPRINT
LESS SOIL COMPACTION

PROFILED TIE BAR
INCREASED LUG STABILITY ELIMINATE LUG SHUFFLING
ELIMINATE LUG BASE CRACK



RRT 500 R-1W

TRACTOR RADIAL R-1W TYRES - FARM XTREME

- HIGH/EXCESS TYRE VOLUME WITH LOW INFLATION PRESSURE PROVIDES HIGH TRACTION AND MINIMUM SOIL COMPACTNESS.
- BEST IN SOIL TILLAGE AND ON ROAD APPLICATION.
- STRONG CARCASS, EXTRA LUG WIDTH WITH EXCELLENT COMPOUND FOR LONGER LIFE.
- EXCELLENT STABILITY AND DRIVING COMFORT IN THE FIELD AND ON THE ROAD APPLICATION.

TYRE SIZES												
16"	18"	20"	24"	26"	28"	30"	32"	34"	36"	38"	42"	46"
240/70R16	280/70R18	250/85R20	250/85R24	480/70R26	250/85R28	380/85R30	320/85R32	320/85R34	320/85R36	320/85R38	480/80R42	420/80R46
260/70R16	320/65R18	260/70R20	280/85R24		280/85R28	420/70R30		380/85R34	340/85R36	340/85R38	520/85R42	480/80R46
280/70R16	340/65R18	280/70R20	320/70R24		320/85R28	420/85R30		420/85R34		380/80R38	580/70R42	520/85R46
320/65R16		280/85R20	320/85R24		320/70R28	460/85R30		460/85R34		380/85R38	620/70R42	
		300/70R20	340/85R24		340/85R28	480/70R30		480/70R34		400/75R38	710/70R42	
		320/70R20	360/70R24		360/70R28	520/70R30		520/70R34		420/85R38		
		320/85R20	380/85R24		380/85R28	600/70R30				460/85R38		
		340/65R20	380/70R24		380/70R28	710/55R30				480/70R38		
		340/80R20	420/65R24		420/85R28					520/85R38		
		360/70R20	420/70R24		420/70R28					520/70R38		
		380/70R20	420/85R24		420/65R28					580/70R38		
		440/65R20	480/70R24		440/65R28					650/85R38		
					480/70R28					710/70R38		
					600/70R28							

Traction

Roadability

Load Carrying Capacity

Soil Protection

RRT500
FARM XTREME

MRL®
taking you further

PREMIUM SIDEWALL

www.mrltires.com